Packed Column Inlet Conversion Kits

Converting Packed Inlets to Capillary Column Use

Two types of inlet conversion kits are available for a ¹/₄-inch packed column injection port to fit either 0.32 or 0.53mm ID capillary columns: the Vu-Tight liner and the Uniliner® liner with adaptor (next page). The Vu-Tight liner fits directly into the ¹/₄-inch injection port and allows visual confirmation of the connection between the column and the liner. The Uniliner® liner and adaptor work together to allow either direct or on-column injection when using 0.53mm ID columns. Both systems incorporate a Press-Tight® connection between the liner and column inlet, minimize dead volume, and reduce solvent peak tailing.

Features of Both Conversion Kits:

- Fit Agilent, Varian, and other common GCs with ¹/₄-inch packed column injection ports (with maximum insertion depth of 4 inches).
- · Install easily within fifteen minutes.
- Accommodate either 0.32 or 0.53mm ID fused silica columns (tubing OD \geq 0.5mm).
- · Liners are deactivated and extremely inert.
- Liners designed to accept dirty samples are available for either system.
- Press-Tight® connections between the liner and column inlet minimize dead volume, reduce solvent peak tailing, and sharpen early-eluting components.

Vu-Tight Inlet Liners for 1/4-Inch Packed Injection Port Conversion

- Visually observe the Press-Tight® connection between the column end and liner.
- Fit 0.32 and 0.53mm ID capillary columns (column ODs from 0.5mm to 0.8mm).
- Slotted top prevents obstruction of carrier gas flow.
- · Two designs available.
- Operate in the direct injection mode.






it's a fact

Vu-Tight Inlet Liners

The ¹/-rinch Vu-Tight liner fits directly into a ¹/-rinch injection port. The connection between the liner and the column is in the GC oven, allowing visual confirmation of the seal. Problems, such as a crushed column end in the Press-Tight® taper, can be detected easily, making proper installation worry-free. The Cyclo Vu-Tight liner prevents non-volatile residue from contaminating the column.



Vu-Tight Inlet Liners for 1/4-Inch Packed Injection Port Conversion

Can easily be packed with wool for dirty samples.

Description	qty.	cat.#	
Vu-Tight DI Liner	ea.	20342	
Vu-Tight DI Liner	5-pk.	20343	
Vu-Tight DI Liner	25-pk.	20344	

Cyclo Vu-Tight DI Liner (1/4-inch OD)

Ideal for dirty samples. Spiral bore prevents nonvolatile residue from contaminating the column.

Description	qty.	cat.#	
Cyclo Vu-Tight DI Liner	ea.	20787	
Cyclo Vu-Tight DI Liner	5-pk.	20788	

Vu-Tight Installation Fittings Kit

Includes a ¹/₄-inch stainless steel nut and graphite ferrule for attaching the liner to the GC inlet and a ¹/₄ to ¹/₁₅-inch stainless steel reducer, plus a ¹/₄-inch and 0.5mm ID graphite ferrule for attaching the column to the liner.

Description	qty.	cat.#	
Vu-Tight Installation Fittings Kit	kit	20504	



