

Split Type Syringe Pump SPM



4.3 inch touch screen control, compact design. Display 8 pump units working parameters and working state in same screen. Friendly interface, easy operation. Split design, mainly for laboratory.


Introduction

1. Each unit working independently, can set one or some units freely. Each unit can infuse or withdraw different volume in same time or different time.

Features

1. Each unit working independently, can set one or some units freely. Each unit can infuse or withdraw different volume in same time or different time.
4.3 inch touch screen control, compact design. Display 8 pump units working parameters and working state in same screen. Friendly interface,
2. Intelligent calibration, ensure infuse volume accuracy. Online micro adjusting function, convenient to adjust the volume of one units, decrease volume error.
3. Real time monitor, animate display monitor result. Controller can receive traffic alarm of each unit.
4. Back distance setting, can exclude bubbles inside syringe, improve volume accuracy.
5. Fast forward and backward function used for loading syringe, washing and unlock traffic protection.

Interface Display



Technical Specifications

Working mode(Five)	Infusion, withdrawal, infusion/withdrawal, withdrawal/infusion
Pump unit	1-8 optional
Syringe size	0.5 μ L-60mL
Syringe selection	Available of the mainly manufacturer, type and syringe from, also can define syringe ID in same time
Linear speed range	1 μ m/min-132mm/min(Flow rate=Linear speed* syringe inner cut area)
Min. linear rate	1 μ m/min
Linear force	\geq 16Kgf
Max. stroke	90mm
Stoke resolution	0.078 μ m/ μ step
Accuracy	Stroke \geq 30% maximum stroke,Error \leq \pm 0.5%
Back distance	0.01-5mm
Working mode	Independent working mode
Stored modes	Can save 10 group working modes
Display	Industrial grade 4.3" LCD color display
Control method	Touch screen and Mechanical keypad
Power-off memory	Display the previous data parameter after power on again
Output	OC gate signal output,used to indicate running status and direction
External control signal	Start/stop signal,active switch signal:(5-24V)
Communication interface	RS232/RS485, Modbus protocol(RTU mode)
Controller Power supply	DC5V/10W
Pump unit power supply	DC24V/24W
Condition temperature	0-40 $^{\circ}$ C
Relative humidity	<80%
IP rate	IP31
Controller dimension	160 \times 150 \times 95 (mm)
Controller weight	1kg
Pump unit dimension	257 \times 110 \times 131 (mm)
Pump unit weight	2.6kg

Dimension Drawing (Unit:mm)

