LUER TO THREAD: Male

LUER TO THREAD:

Female

Material Suffix Key

-1 White Nylon	-10 Acetal
-4 Green Nylon	-5 Blue Nylon
-6 Natural Polypropylene	-62 Black Polypropylene
-81 Lace White ABS	-9 Clear Polycarbonate

-2 Black Nylon -3 Red Nylon -06 Orange Nylon -07 Yellow Nylon -6005 Animal-Free Polypropylene -8003 Natural ABS -9002 Radiation Stable Polycarbonate -J1A Natural Kynar PVDF

14MTLL (-1 -2 -6) Male Luer Integral Lock Ring with 9/16" Hex to 1/4-18 NPT Thread



XFTL (-1 -6 -9 -J1A)

Female Luer Lug Style with 1/4" Hex to 10-32 Special Tapered Thread



KFTL (-1 -6 -9 -J1A)

Female Luer Lug Style with 1/4" Hex to 10-32 UNF Thread



SFTL (-1 -6 -9 -J1A)

Female Luer Lug Style with 5/16" Hex to 1/4-28 UNF Thread



18FTLL (-1 -6 -J1A)

Female Luer Thread Style with 7/16" Hex to 1/8-27 NPT Thread



18LFTLL (-1 -4 -5 -6 -J1A -62)

Female Luer Thread Style Elbow with 7/16" Hex to 1/8-27 NPT Thread



PANEL MOUNTS:

Female Thread Style and Lug Style Luer

FTLLB210 (-1 -2 -6 -9 -J1A)

Female Luer Thread Style Panel Mount 1/4-28 UNF to 200 Series Barb, 1/16" (1.6 mm) ID Tubing



FTLLB220 (-1 -2 -6 -9 -J1A)

Female Luer Thread Style Panel Mount 1/4-28 UNF to 200 Series Barb, 3/32" (2.4 mm) ID Tubing



FTLLB230 (-1 -2 -6 -9 -J1A)

Female Luer Thread Style Panel Mount 1/4-28 UNF to 200 Series Barb, 1/8" (3.2 mm) ID Tubing



XMLRL (-1 -6 -9 -9002)

Male Luer with 1/4" Hex to 10-32 Special Tapered Thread (May be used with separate rotating lock ring; FSLLR)



SMLRL (-1 -6 -9 -J1A)

Male Luer with 5/16" Hex to 1/4-28 UNF Thread (May be used with separate rotating lock ring; FSLLR)



BSMLRL (-6 -J1A)
Male Luer with 5/16" Hex to 1/4-28 Bottom-Sealing Thread (May be used with separate rotating lock ring; FSLLR)



LUER TO THREAD:

Female

XFTLL (-1 -6 -9 -J1A)

Female Luer Thread Style with 1/4" Hex to 10-32 Special Tapered Thread



KFTLL (-1 -6 -9 -J1A)

Female Luer Thread Style with 1/4" Hex to 10-32 UNF Thread



SFTLL (-1 -2 -6 -9 -J1A)

Female Luer Thread Style with 5/16" Hex to 1/4-28 UNF Thread



BSFTLL (-1 -6 -J1A)

Female Luer Thread Style with 5/16" Hex to 1/4-28 UNF Bottom Sealing Thread



VALUE PLASTICS; INC.