## **Microelectric Actuators for Selectors**

- CE certified
- Direction reversal
- Position indication
   LED display
   RS-232 output
   BCD 5V negative true output
- Manual control
   Step and home functions
   Clockwise and counterclockwise functions
- Remote control
   Step and home functions with contact closure
   Direct position access with BCD 5V negative true input
   Direct position access with RS-232 input (RS-485 optional)
- Automatic self-alignment with keyed valves and standoffs

One actuator can be used on any selector, from 2 to 96 positions – you tell the actuator how many stops to make through its 360° of rotation. So you can stock only one type of actuator even if you have 4, 6, 8, 10, 12, and 16 position valves. Valve position memory is maintained even in the event of a power failure.

The direction reversal feature means that if a 6 position stream selection valve is on stream 1 and you select stream 6, you have the option of stepping "backwards" to stream 6 instead of passing through 2, 3, 4, and 5. The RS-232 input offers various commands like position access, direction control, shortest route, etc. (The RS-232 cable must be ordered separately.)

# MORE INFORMATION

Microelectric actuators For two position . . . . 189

## **Mounting Hardware**

Closemount
hardware..... page 208
Right angle drive.....204
Standoff assembly....205
Standoff mounting
hardware.......205

#### **ORDER TIP**

To purchase a *valve with a microelectric actuator installed*, see valve ordering information.

#### Valco

Injectors and valves .... pp 102-116 Selectors ..... 122-133

## Cheminert

Injectors and valves ..... 152-167 Selectors ..... 170-177

CHROMalytic TECHnology Pty Ltd AUSTRALIAN Distributors e-mail: sales@chromtech.net.au Tel: 03 9762 2034